

FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

3E Series Compact Utility Tractors - 3025E, 3032E, 3038E

ENGINE

PRIMARY AIR FILTER – [M131802](#)

SECONDARY AIR FILTER – [M131803](#)

Check or replace every 600 hours or as required.

ENGINE

DIESEL PARTICULATE FILTER (DPF)
(S/N 610001 -)

3032E – [MIA884117](#)

3038E – [MIA883483](#)

See your John Deere™ dealer or qualified service provider.

FILTER PAK

3025E, 3032E (S/N - 610000), 3038E
(S/N - 610000) – [LVA21128](#)

3032E (S/N 610001 -), 3038E
(S/N 610001 -) – [LVA21037](#)

Each kit contains oil filter, air filter, fuel filter, and hydraulic filter, offering a complete solution for your maintenance needs to keep your tractor running at peak performance.

ENGINE

FUEL FILTER

3025E, 3032E (S/N - 610000), 3038E
(S/N - 610000) – [MIU800645](#)

3032E (S/N 610001 -), 3038E
(S/N 610001 -) – [MIU803127](#)

Replace every 400 hours or annually, whichever occurs first.

ENGINE

OIL FILTER – [M806419](#)

Replace every 200 hours or annually,
whichever occurs first.

(Click here for [capacity](#))

ENGINE

FUEL/WATER SEPARATOR

3025E, 3032E (S/N - 610000), 3038E
(S/N - 610000) – [M811032](#)

3032E (S/N 610001 -), 3038E
(S/N 610001 -) – [MIU802421](#)

Replace every 400 hours or annually,
whichever occurs first.

TRANSMISSION/HYDRAULIC

OIL FILTER – [LVA16054](#)

Replace after initial 50 hours,
then every 400 hours.

(Click here for [capacity](#))

HYDRAULIC

OIL FILTER – [LVA14703](#)

Replace every 400 hours.

(Click here for [capacity](#))



JOHN DEERE

Genuine Parts and Service

CAPACITIES

3E Series Compact Utility Tractors - 3025E, 3032E, 3038E

CAPACITIES (Approximate):

Fuel Tank:

..... 23.5 L (6.2 gal)

Cooling System:

Cool-Gard™ II

3025E, 3032E 4.1 L (4.3 qt)

3038E 4.8 L (5.1 qt)

Crankcase with Filter:

Plus-50™

..... 4 L (4.2 qt)

Transmission and Hydraulic System:

Hy-Gard™

..... 21 L (5.5 gal)

Front Axle:

Hy-Gard™

..... 3.2 L (3.4 qt)

[Return to Filter Overview](#)