

FILTER OVERVIEW WITH SERVICE INTERVALS


6010 Series tractors

CAB

KIT ACTIVATED CARBON FILTER

- only for first installation -
(6110 - 6410,
6310S - 6510S) - [AL158985](#)

Never clean dry or wet!




ACTIVATED CARBON FILTER

(6110 - 6410, 6310S - 6510S)

[L156235](#) - left hand side,
[L156236](#) - right hand side

Never clean dry or wet!

Replace every **500 hours**,
once every year and as required




CAB

RECIRCULATION AIR FILTER ELEMENT

(6110 - 6410,
6310S - 6510S) - [AL71259](#)

Please order 2!

Replace every **1,500 hours**
or every **2 years** and as required



HYDRAULICS

(without JD IVT)

HYDRAULIC OIL FILTER (6110 - 6410,
6110L - 6510L, 6310S - 6510S) - [AL156625](#)
With 25 cm³ resp. 1.53 inch³ hydraulic pump

HYDRAULIC OIL FILTER (6110 - 6410,
6110L - 6510L, 6310S - 6510S) - [RE34958](#)
With 41 cm³ resp. 2.50 inch³ hydraulic pump

Replace after **100, 750 hours**
and then every **750 hours**



TRANSMISSION (without JD IVT)

OIL FILTER - [AL156625](#)
length = 158 mm/6.22 inch

Replace after **100, 750 hours**
and then every **750 hours**



ENGINE

OIL FILTER (all models) - [RE59754](#)

Replace after the first **100 hours**
and then every **250 hours**



CAB

FRESH AIR FILTER - HEAVY DUTY (6110 - 6510,
6310S - 6510S, 6405, 6605) - [AL177185](#)

Please order 2, for "Advantage" tractors order 1!

AIR FILTER - STANDARD
(6110 - 6510, 6310S - 6510S, 6405, 6605) - [AL177184](#)

Please order 2, for "Advantage" tractors order 1!

Replace every **1,500 hours** or every **2 years**
and as required




ENGINE

FUEL FILTER

(all models) - [RE62419](#)
(length = 109 mm)

PRE FUEL FILTER
(all models) - [RE509208](#)

Replace every **500 hours**



ENGINE

SAFETY ELEMENT AIR FILTER

(6110 - 6410, 6110L - 6510L,
6310S - 6510S, 6405) - [AL78224](#);
(6605) - [AL78870](#)

Do not clean

Replace every **1,500 hours**
or every **2 years** and as required

ENGINE

MAIN CARTRIDGE AIR FILTER

(6110 - 6410, 6110L - 6510L,
6310S - 6510S, 6405) - [AL78223](#);
(6605) - [AL78869](#)

Replace every **1,500 hours**
or every **2 years** and as required
(can be cleaned up to five times)

FRONT PTO

OIL FILTER FRONT PTO

(6110 - 6410,
6310S - 6510S) - [L114404](#)

Replace every **750 hours**



JOHN DEERE

Genuine Parts and Service