

# FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

## 7030 Small Frame Series Tractors (7130, 7230, 7330)

**CAB**  
**KIT, ACTIVATED CARBON FILTER**  
[AL158986](#)

Never clean dry or wet!

Replace every 500 hours, once every year and as required.



**CAB**  
**ACTIVATED CARBON FILTER**  
[L209778](#)

Please order 2.

Never clean dry or wet!

Replace every 500 hours, once every year and as required.



**CAB**  
**FRESH AIR FILTER - HEAVY-DUTY**  
[AL177185](#)

Please order 2.

**AIR FILTER - STANDARD**  
[AL177184](#)

Please order 2.

Replace every 1500 hours or every 2 years and as required.



**CAB**  
**RECIRCULATION AIR FILTER**  
[L214634](#)

With air conditioning; please order 2.

[L152026](#)

Without air conditioning; please order 2.


Replace every 1500 hours or every 2 years and as required.



**HYDRAULICS**  
**FILTER ELEMENT**  
[AL169573](#)


Replace after 100 hours, then every 750 hours.

(Click here for [capacity](#))



**ENGINE**  
**MAIN CARTRIDGE AIR FILTER**  
[AL172780](#) (Lgth. 183 mm)  
[AL172781](#) (Lgth. 284 mm)

Replace every 1500 hours or every 2 years and as required.



**ENGINE**  
**SAFETY ELEMENT AIR FILTER**  
[AL150288](#)

Replace every 1500 hours or every 2 years and as required.

**TRANSMISSION**  
[AL156625](#)

Replace after 100 hours, then every 750 hours.

(Click here for [capacity](#))



**ENGINE**  
**OIL FILTER**  
[RE504836](#)

Replace after 100 hours, then every 500\* hours.

(Click here for [capacity](#))

\* The service interval is 250 hours if PLUS-50™ oil and genuine John Deere™ filters are not used.



**ENGINE**  
**PRIMARY FUEL FILTER**  
 (7130, MY07-MY09, 6068L ENGINE) [RE541922](#)  
 (7130, MY10-, 4045L ENGINE) [RE546336](#)  
 (7230-7330) [RE529643](#)

Replace every 500 hours.



**ENGINE**  
**FINAL FUEL FILTER**  
 (7130, MY07-MY09, 6068L ENGINE) [RE522878](#)  
 (7130, MY10-, 4045L ENGINE) [RE526557](#)  
 (7230-7330) [RE522878](#)

Replace every 500 hours.



**JOHN DEERE**

Genuine Parts and Service

# CAPACITIES

## 7030 Small Frame Series Tractors (7130, 7230, 7330)

### CAPACITIES (Approximate):

#### Fuel Tank:

7130-7230 .....	207 L (54.7 gal)
7330.....	250 L (66 gal)
7330.....	325 L (85.9 gal)

#### Cooling System:

##### Cool-Gard™ II

7130 without Cab.....	26.5 L (7 gal)
7130 with Cab.....	29 L (7.7 gal)
7230-7330 without Cab .....	31.1 L (8.2 gal)
7230-7330 with Cab .....	33.6 L (8.9 gal)

#### Crankcase with Filter:

##### Plus-50™ II

7130.....	16 L (4.2 gal)
7230, 7330.....	19.5 L (5.2 gal)

#### Front-Wheel Drive:

##### Hy-Gard™

Axle Housing .....	8.2 L (8.7 qt)
Final Drives (7130-7230).....	2.9 L (3.1 qt)
Final Drives (7330).....	1.7 L (1.8 qt)

#### Transmission and Hydraulic System:

##### Hy-Gard™

SyncroPlus™ (7130-7230).....	52 L (13.7 gal)
Power Reverser™ (7130-7230).....	52 L (13.7 gal)
PowrQuad™.....	52 L (13.7 gal)
PowrQuad™ Plus.....	52 L (13.7 gal)
Extra with Creeper Transmission.....	1 L (1.1 qt)
Extra with Front-Wheel Drive.....	3 L (3.2 qt)

[Return to Filter Overview](#)

