

FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

9000 Series Tractors

ENGINE

SECONDARY AIR FILTER (9100-9400) – [RE63932](#)

Replace annually and as required.

ENGINE

PRIMARY AIR FILTER (9100-9400) – [AH148880](#)

Replace annually and as required.

ENGINE

OIL FILTER (9100) – [DZ101880](#)

OIL FILTER (9200-9400) – [RE58935](#)

Replace after 100 hours and then every 250 hours.

Initial oil and filter change is 100 hours maximum of operation. Scheduled interval can be extended to 375 hours if PLUS-50™ oil and a John Deere filter are used.

(Click here for [capacity](#))

TRANSMISSION

OIL FILTER (9100-9400) – [RE174130](#)

Replace every 750 hours and as required.

(Click here for [capacity](#))

ENGINE

PRE-FUEL/WATER SEPARATOR (9100) – [RE508633](#)

FUEL PRIMARY (9100) – [AR86745](#)

PRIMARY FUEL FILTER (9200-9400; early two-filter style) – [RE502203](#)

SECONDARY FUEL FILTER (9200-9400; early two-filter style) – [RE506428](#)
9200 up to engine serial-no. -3713
9300/9400 up to engine serial-no. -10637

FUEL FILTER

(9200-9400; single filter system) – [RE507284](#)
9200 from engine serial no. 3714 up to 29999
9300/9400 from engine serial no. 10638 up to 29999

FUEL FILTER

(9200-9400; single filter system) – [RE507284](#)
9200/9300/9400 from engine serial no. 30000

Replace every 750 hours.

HYDRAULICS

AXLE LUBE FILTER, CLEANUP (9100-9400) – [AL118036](#)

AXLE LUBE FILTER (9100-9400) – [AL156625](#)

Replace after 100 and 750 hours, and then every 750 hours.

(Click here for [capacity](#))

HYDRAULICS

OIL HYDRAULIC (9100-9400) – [RE174130](#)

Replace every 750 hours and as required.

(Click here for [capacity](#))

CAB

RECIRCULATION AIR FILTER (9100-9400) – [RE70742](#)

9100 up to engine serial no. 030000
9200 up to engine serial no. 001674
9300 up to engine serial no. 001752
9400 up to engine serial no. 002395

Clean every 250 hours and replace annually.

RECIRCULATION AIR FILTER (9100-9400) – [RE187966](#)

9100 from engine serial no. 030001
9200 from engine serial no. 001675
9300 from engine serial no. 001753
9400 from engine serial no. 002396

ACTIVATED CARBON RECIRCULATION

AIR FILTER (9100-9400) – [RE199682](#)

Do NOT clean. Change annually, after 500 hours, or as required.

CAB

FRESH AIR FILTER, HEAVY DUTY (9100-9400) – [RE67829](#)

AIR FILTER, STANDARD (9100-9400) – [RE24619](#)

Replace annually and as required.

CAB

ACTIVATED CARBON AIR FILTER (9100-9400) – [RE199681](#)

Do NOT clean. Change annually, after 500 hours, or as required.

ENGINE

AIR, HYDRAULIC RESERVOIR FILTER (9100-9200) – [AT101565](#)

Replace annually and as required.

(Click here for [capacity](#))



JOHN DEERE

Genuine Parts and Service

CAPACITIES

9000 Series Tractors

CAPACITIES (Approximate):

Fuel Tank:

..... 969 L (256 gal)

Cooling System:

Cool-Gard™

9100..... 58 L (14.5 gal)

9200-9300-9400 60 L (16 gal)

Crankcase:

Plus-50™

9100..... 30 L (8 gal)

9200-9300-9400 42 L (11 gal)

12 and 24 Speed Transmission:

Hy-Gard™

Without PTO (Capacity Includes Axles)..... 129 L (34.5 gal)

With PTO (Capacity Includes Axles)..... 131 L (35 gal)

Powershift Transmission:

Hy-Gard™

Without PTO 51 L (13.5 gal)

With PTO 53 L (14 gal)

Axles 102 L (27 gal)

Hydraulic System:

Hy-Gard™

Without Hitch 98 L (26 gal)

With Hitch 102 L (27 gal)

[Return to Filter Overview](#)