

# FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

## 9020 Series Tractors

### ENGINE

**SECONDARY AIR FILTER (9120-9620) – [RE63932](#)**

Replace annually and as required.

### ENGINE

**PRIMARY AIR FILTER (9120-9620) – [AH148880](#)**

Replace annually and as required.

### ENGINE

**OIL FILTER (9120) – [RE509672](#)**

**OIL FILTER (9220-9620) – [RE58935](#)**

Replace after 100 hours and then every 250 hours.

Initial oil and filter change is 100 hours maximum of operation. Scheduled interval can be extended to 375 hours if PLUS-50™ oil and a John Deere filter are used.

(Click here for [capacity](#))

### TRANSMISSION

**OIL FILTER (9120-9620) – [RE174130](#)**

Replace after 100 and 750 hours, and then every 750 hours.

(Click here for [capacity](#))

### ENGINE – 9220-9620

Single filter system – use with 6125HRW13/6125HRW15

**FUEL FILTER – [RE507284](#)**

Replace after 100 hours, then every 500 hours

Two filter system – use with 6125HRW16/6125HRW17/6125HRW18

**PRIMARY FUEL FILTER – [RE515345](#)**

**SECONDARY FUEL FILTER – [RE506428](#)**

Replace every 250 hours.

### ENGINE – 9120

Single filter system, up to engine serial no. 232462

**FUEL FILTER – [RE522372](#)**

**FUEL PRE FILTER – [R502778](#)**

Replace after 100 hours, then every 500 hours

Two filter system, from engine serial no. 232463

**PRIMARY FUEL FILTER – [RE531703](#)**

**SECONDARY FUEL FILTER – [RE522688](#)**

Replace every 250 hours.

### CAB

**RECIRCULATION AIR FILTER (9120-9620) – [RE187966](#)**

Clean every 250 hours and replace annually.

### CAB

**ACTIVATED CARBON RECIRCULATION**

**AIR FILTER (9120-9520) – [RE199682](#)**

Do NOT clean. Change annually, after 500 hours, or as required.

### CAB

**OIL, HIGH FLOW**

(Scraper Tractor, 9320-9520) – [T175002](#)

Replace every 750 hours.

(Click here for [capacity](#))

### CAB

**FRESH AIR FILTER, HEAVY DUTY (9120-9620) – [RE67829](#)**

**AIR FILTER, STANDARD (9120-9620) – [RE24619](#)**

Clean every 250 hours and replace annually.

### CAB

**ACTIVATED CARBON AIR FILTER (9120-9520) – [RE199681](#)**

Do NOT clean. Change annually, after 500 hours, or as required.

### HYDRAULICS

**AIR, HYDRAULIC RESERVOIR (9120-9620) – [AT101565](#)**

Replace every 750 hours.

(Click here for [capacity](#))

### HYDRAULICS

**HYDRAULIC OIL FILTER (9120-9620) – [RE174130](#)**

Replace after 100 and 750 hours, and then every 750 hours.

(Click here for [capacity](#))



**JOHN DEERE**

Genuine Parts and Service

# CAPACITIES

## 9020 Series Tractors

### CAPACITIES (Approximate):

#### Fuel Tank:

..... 1026 L (270 gal)

#### Cooling System:

##### Cool-Gard™

9120-9220 ..... 52 L (13.75 gal)

9320-9420-9520-9620 ..... 60 L (16 gal)

#### Crankcase:

##### Plus-50™

9120 ..... 26.5 L (7 gal)

9220-9320-9420-9520-9620 ..... 42 L (11 gal)

#### 24 Speed Transmission:

##### Hy-Gard™

Without PTO (Capacity Includes Axles)..... 129 L (34 gal)

With PTO (Capacity Includes Axles)..... 131 L (35 gal)

#### Powershift Transmission:

##### Hy-Gard™

Without PTO (Capacity Includes Axles)..... 134 L (35.4 gal)

With PTO (Capacity Includes Axles)..... 138 L (36.4 gal)

#### Hydraulic System:

##### Hy-Gard™

Without Hitch-Standard ..... 103 L (27 gal)

With Hitch-Standard ..... 106 L (28 gal)

Without Hitch-High Flow ..... 113.5 L (30 gal)

With Hitch-High Flow ..... 117 L (31 gal)

[Return to Filter Overview](#)

